



Screen printing, UV based transparent varnish with stone effect. It is suitable for packaging ennoblement and for any type of customizing.

Key features and substrates:

- Matt finishing
- Rough effect
- High reactivity
- Excellent scratching fastness

Instructions for use:

Stir the varnish thoroughly before use.
If necessary, it is possible to reduce viscosity by adding max. 5% UV REACTIVE THINNER

Screens and yield:

It is recommended to print UV STONE with 43-77 th/cm
Yield: by using 77 th/cm screens approx. 40 sqm per KG

Drying and curing:

UV STONE is a very reactive UV varnish. By means of a Hg, 80-120 W/cm lamp curing speed will be approx. 15-20 m/min.
By using a lower power light source it is recommended to reduce curing speed.

Cleaning:

Clean working tools with suitable washing solvents, like 109 and 114 (cod. 181109 and cod. 181114)

Application:

- Particularly suitable for:
- Paper and cardboard
 - PVC, PET, PETG
 - ABS, PES, PC, PMMA

Storage and shelf life:

Protect from extreme temperatures and from direct sunlight.
It is recommended to keep the original closed container in a fresh, dry and dark place.
Shelf life: 12 months

Packing:

Metal cans: 1 and 5 KG

NOTE

Our technical advice whether spoken, written or through test trials corresponds to our current knowledge and provides information about our products and use. ENGLER ITALIA cannot, however, guarantee the finished results because ENGLER ITALIA exercises no control over those factors which may determine the use and application of the product at the user's headquarter.

Unless specifically agreed in writing, ENGLER ITALIA is not, therefore, liable for any loss or damage deriving from an unauthorized use of the product.

The selection and testing of the product is exclusively user's responsibility. Should any liability claim arise, they shall be limited to the value of goods delivered by ENGLER ITALIA and utilised by user with respect to any and all damages not caused intentionally or by gross negligence.