



Water based, transparent and high viscosity printing paste. It is suitable to obtain overprinting glossy effects or to get a slightly gummy, soft effect with thickness (by using the proper additive).

Key features and substrates:

- Printed surface looks glossy and smooth, flexible (not elastic) and with very high washing fastness (90°C and drying cleaning)
- Intensity of the final result is directly related to the quantity of printed product
- Suitable for ironing
- Keeps glossy during hot forming
- Suitable for stone wash process of denim if used as resist dyeing agent

Instructions for use:

Product is ready to use

- You can add 5% Lacprint pigments or special ones to LACPRINT HS Transparent (cod. 301904)
- To slow down drying, it is recommended to use Retarder 03 (max. 5%)
- To thicken the paste, it is recommended to add THICKENER 516; then mix the product thoroughly

Screens:

- It is usually recommended to print the products with 77 th/cm screens.
- When mixed with pigments it is necessary to select the appropriate screen depending on pigment particle size
- To print high thickness effects it is recommended to use 12-24 th/cm screen

Drying and curing:

At room temperature for 24 h
Curing at 140-150°C for 3 min

When printing high thickness, it is recommended to dry at room temperature or max. at 80°C and then proceed with curing

If mixing the product with pigment it is recommended to wait 30 min. after printing before starting curing

When printed to coated fabrics, curing is usually not necessary

Cleaning:

Clean tools and screens with water

Applications:

Special colour effects for cotton, poly-cotton and silk fabrics

Storage and Shelf-life:

Protect from extreme temperatures.
It is recommended to keep the original closed container in a dry and fresh place. Frost sensitive

Shelf life: 12 months

Packing:

Plastic cans and drums:
5 KG
20 KG
50 KG

NOTE

Our technical advice whether spoken, written or through test trials corresponds to our current knowledge and provides information about our products and use. ENGLER ITALIA cannot, however, guarantee the finished results because ENGLER ITALIA exercises no control over those factors which may determine the use and application of the product at the user's headquarter.

Unless specifically agreed in writing, ENGLER ITALIA is not, therefore, liable for any loss or damage deriving from an unauthorized use of the product.

The selection and testing of the product is exclusively user's responsibility. Should any liability claim arise, they shall be limited to the value of goods delivered by ENGLER ITALIA and utilised by user with respect to any and all damages not caused intentionally or by gross negligence.